## DialogiP

Asynchronous electrical machine with regulated power output - has field winding divided into even number of partial windings connected in polygonal circuit supplied at each connection node pair with respective periodic current

Patent Assignee: PILLER GMBH; MUEHMEL FA EUGENIE

**Inventors:** BAUKNECHT G

## **Patent Family**

Patent Number	Kind	Date	Application Number	Kind	Date	Week	Туре
WO 9601000	A1	19960111	WO 95EP2506	Α	19950628	199608	В
DE 4422622	<b>A</b> 1	19960125	DE 4422622	A	19940628	199609	
EP 715778	A1	19960612	EP 95925774	Α	19950628	199628	
			WO 95EP2506	Α	19950628		
EP 715778	B1	20000412	EP 95925774	Α	19950628	200023	
			WO 95EP2506	Α	19950628		
DE 59508171	G	20000518	DE 508171	Α	19950628	200031	
			EP 95925774	Α	19950628		
			WO 95EP2506	Α	19950628		

Priority Applications (Number Kind Date): DE 4422622 A ( 19940628)

Cited Patents: DE 2748515

## **Patent Details**

Patent	Kind	Language	Page	Main IPC	Filing Notes				
WO 9601000	A1	G	56	H02K-003/28					
Designated States (National): US									
Designated States (Regional): AT BE CH DE DK ES FR GB GR IE IT LU MC NL PT SE									
DE 4422622	A1		6	H02K-017/12					
EP 715778	A1	G	1	H02K-003/28	Based on patent WO 9601000				
Designated States (Regional): AT BE DE DK ES FR GB GR IE IT LU NL PT SE									
EP 715778	B1	G		H02K-003/28	Based on patent WO 9601000				
Designated States (Regional): AT BE DE DK ES FR GB GR IE IT LU NL PT SE									
DE 59508171	G			H02K-003/28	Based on patent EP 715778				
					Based on patent WO 9601000				

## Abstract:


WO 9601000 A

The machine has a rotor and a stator, one of which has a field winding (60) with at least two winding strands, coupled to a current or voltage source for providing a circulating polar field. The winding is divided into an even number of four or more partial windings (S), interconnected in a polygonal circuit.

The polygonal circuit has the same number of connection nodes (V1-V6) as the number of partial windings, with opposing connection node pairs used as a supply terminal pair. Each supply terminal pair is inserted in a respective supply circuit for providing a periodic current.

ADVANTAGE - Improved power characteristics.

Dwg.4/19



Derwent World Patents Index © 2003 Derwent Information Ltd. All rights reserved. Dialog® File Number 351 Accession Number 10580711

**BEST AVAILABLE COPY**